



AC/AC Frequency Converters

FTT12000R Series 3Ø to 3Ø Frequency Converters

Benefits

- Ultra-Quiet
- Power sensitive electronics without interference
- Rugged & Reliable
- Ensure years of safe and trouble free operation

Applications

- Aviation / Marine
- Electric Utilities and Substations
- Telecom Power Plants
- Manufacturing Locations
- Steel Mills
- Military Applications (COTS)
- Industrial Controls
- OEM Applications
- Solar / Alternative Power Systems
- Fuel Cells

Description

The FTT12000R AC/AC frequency converter provides 3-phase power from a 3-phase line outlet. The standard unit delivers 3-phase outputs of 208rms, 380Vrms or 415Vrms (PH-PH) continuous at 50, 60, or 400Hz.

The floating outputs are isolated from each other and can be connected in a 'Y' configuration or left as three individual outputs. In 'Y' configuration, the centre point (neutral) can be grounded.

The unit features full electronic protection, high efficiency and low input and output noise.

Features

- Sinusoidal wave shape
- Isolated, floating output
- 12000VA output power
- Full electronic protection
- Telecom quality
- Field-proven design topology

FTT12000R Series 3Ø to 3Ø AC/AC Frequency Converters

Specification

| | |
|------------------------------------|---|
| Input Voltage | 208V or 380V, 3-phase 47 ... 410Hz range (Consult factory for other inputs) |
| Input Protection | Thermal fuse, Inrush current limiting |
| Isolation | 2250 VDC input to chassis / 2250 VDC input to output / 2250 VDC output to chassis |
| Output Voltages | 208rms / 3-phase continuous or 380Vrms / 3-phase continuous or 415Vrms / 3-phase continuous at 50, 60, or 400Hz The centre point (neutral) is floating - it can be grounded Consult factory for other voltages and frequencies |
| Wave Form | Sinusoidal |
| Total Harmonic Distortion | Less than 5% at full load |
| Efficiency | Min 78% at full load |
| Line Regulation | Maximum 0.5% |
| Load Regulation | Maximum $\pm 6\%$ from 10% load to full load |
| Output Protection | Current limiting with short circuit protection, thermal shutdown with automatic recovery in case of continuous overload or insufficient airflow |
| EMI | EN 55022 Class B (typical) |
| Load Crest Factor | Maximum 3.0 at 90% load |
| Frequency Stability | $\pm 0.1\%$ |
| Operating Temperature Range | 0° C to +50° C (Extended range available, Consult factory) |
| Humidity | 5 - 95% non-condensing |
| Temperature Drift | 0.05% per ° C over operating temperature range |
| Dimensions | 16U x 19" x 15" Rack Mount Enclosure Depth: 17" maximum |
| Connections | Input/output: terminal block |
| Weight | 160 pounds (72.6kg) |
| Safety | Designed to meet C22.2 No. 107.1 - 01, UL 458 and EN60950 Please contact factory for approval status for the requested input/output configuration |

Warranty: Twenty four months subject to application within good engineering practice
Enhancements to these general specifications can be accommodated upon request
Designed to meet common approval requirements. Specifications Subject to Change Without Notice
Designed and Manufactured in Canada

Available from:



8128 River Way, Delta, BC Canada V4G1K5
Tel: 604-946-9981 / Fax: 604-946-8983 / Toll Free: 1-800-668-3884
www.analyticsystems.com
© 2008 Analytic Systems Ware (1993) Ltd.
Subject to Change Without Notice