

Xenon Beacons



ELMDENE

*Security & Fire
Products*

Benefits:

- Extensive range offering more choice
- Low-profile style available
- High efficiency giving maximum light output
- Hard wearing polycarbonate lenses for long life
- Reliable operation and performance
- Ideal for stringent applications such as Fire
- Easy to install
- Reliable for low maintenance and operational costs

Features:

- MAXIMUM LIGHT OUTPUT
- HIGH EFFICIENCY
- TESTED TO IP 65 RATING
- HARD WEARING POLYCARBONATE LENS
- LOW-PROFILE STYLE AVAILABLE
- HF2 SERIES COMES WITH FRESNEL LENS FOR MAXIMUM LIGHT OUTPUT
- WIDE RANGE OF OPERATING VOLTAGES AND POWER OUTPUTS AVAILABLE
- CHOICE OF COLOURED LENSES

*Beacons
you can rely on*

www.elmdene.co.uk



INTRUDER



FIRE






Beacons

Specifications

Type	HF2 Series	HF3 Series
Voltage DC	6, 12, 24, 48	12, 24
Voltage AC	110, 220, 240	
Power Output	0.5 Watt, 1 Watt, 2 Watt, 3 Watt	5 Watt
Current Consumption (12V)	42mA, 84mA, 168mA, 252mA	420 mA
Current Consumption (24V)	21mA, 42mA, 84mA, 126mA	210mA
Flash Rate	1 per Second	1 per Second
Rating	IP 65	IP 65
Lens Material	Polycarbonate	Polycarbonate
Body Material	ABS	ABS
Temperature Range	- 30°C to + 70°C	- 30°C to + 70°C

HF2 SERIES



A B C D E

Dimensions 51mm 75mm 45mm 85mm 90mm

Fixing Details

HF2 Surface Mounting 2 x 4mm

HF2 Flange Mounting 76mm Diameter

ELMDENE INTERNATIONAL LIMITED
 Rodney Road, Fratton, Portsmouth PO4 8SS United Kingdom
 Tel: +44 (0)23 9273 9412 Fax: +44 (0)23 9281 1631
 e-mail: sales@elmdene.co.uk



ELMDENE

Security & Fire
 Products

www.elmdene.co.uk